



## Residential Aluminum Fencing Specifications Chart

### **PANELS**

Material: 6063-T3 aluminum

Rails: 1" x 1" x 0.055" thick

Pickets: 0.59" x 0.59" x 0.05" thick

Picket Spacing: 3- 13/16"

Available Heights: 48", 52", 60" and 72" depending on style

Available Colors: Black

AAMA 2604 Polyester Powder Coating

Warranty: 15 Year Limited Lifetime

Screws: Rust resistant colored head; some styles available as screw-less

All panels are preassembled

Standard Packaging: 5 panels per carton

### **Posts:**

Material: 6063-T3 aluminum

Line/Corner Posts: 2" square x 0.062" thick

End/Gate Posts: 2" square x 0.080" thick (0.125" thick also available)

Available Heights: 72", 79", 84" and 96" depending on style

Available Colors: Black

AAMA 2604 Polyester Powder Coating

Warranty: 15 Year Limited Lifetime

All posts are pre-punched to accept panel rails

Standard Packaging: 6 posts per carton

Post Spacing: 72-1/2" on center

### **Gates:**

Material: 6063-T3 aluminum

Frame: 0.118" thick

Rails: 1" x 1" x 0.055" thick

Pickets: 0.059" x 0.059" x 0.05" thick

Welded frame and picket construction

Available Heights: 48", 52", 60" and 72" depending on style

Available Widths: 4', 5', 6' and 8' depending on style

Available Styles: Straight Top, Arched Top and Rainbow Arch Styles

Available Colors: Black

AAMA 2604 Polyester Powder Coating

Warranty: 15 Year Limited Lifetime